



SHEAR POCKET EXTENDED INTO WALL AND TURNED UP 6" ABOVE THE LEVEL OF THE DECK. POCKET ABOVE DECK IS TURNED AROUND FACE OF WALL AND ANCHORED WITH TERMINATION BAR AND NOSING MATERIAL AGAINST FACE OF WALL.

SEISMIC COLORSEAL EXPANDING FOAM SEALANT, WITH 100% MOVEMENT CAPABILITY, INSTALLED IN WALL AND FLASHED DOWN INTO POCKET. COLORSEAL TO BE RUN UP WALL, OVER TOP, AND DOWN OTHER SIDE.

STANDARD DECK-TO-WALL TERMINATION, (TERMINATION BAR CLAMPS FLANGE TO FACE OF WALL AND IS ENCAPSULATED IN NOSING MATERIAL

SHEAR POCKET (NOTE: GAP WIDENED FOR ILLUSTRATION PURPOSES)

SHEAR POCKET TRANSITION INTO STANDARD TM 2.5 PROFILE. (FIELD-WELDED BY EMSÉAL TECHNICIAN)

EDGE OF FLANGE

EDGE OF NOSING MATERIAL

EMSÉAL JOINT SYSTEMS LTD.

TM 2.5 SHEAR POCKET TRANSITION W/PARAPET BOOT TERMINATION

CD-ROM VERSION 3 FILENAME: ShrPocketParapet

C:\SERVER\DETAILS\THERM\TM\

Copyright 1995, by EMSÉAL Joint Systems, Ltd. All rights reserved.

DRAWN	DATE:	SCALE:	DRAWING
BY: MH	11/17/95	N.T.S.	No:
PART NUMBER:	\008-0-00-00		