

EMSEAL CORPORATION LTD

120 Carrier Drive
Rexdale, ON M9W 5R1
PH : 416-740-2090, FX : 416-740-0233



www.emseal.com

EMSEAL JOINT SYSTEMS LTD

23 Bridle Lane, Suite 3
Westborough, MA 01581-1228
PH: 508-836-0280, FX: 508-836-0281

MATERIAL SAFETY DATA SHEET

PRODUCT: Top Coat 200

MSDS DATE: 2006/11/10

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Top Coat 200

Manufacturer: EMSEAL CORPORATION
Address: 120 Carrier Dr
Toronto, Ontario
M9W 5R1

Emergency Phone: 416-740-2090
Fax: 416-740-0233

SECTION 2: COMPOSITION

EMSEAL Top Coat 200 is composed of polymer modified rubberized asphalt emulsion.

SECTION 3: HAZARDS IDENTIFICATION

This product is not classified as hazardous when used as intended.

SECTION 4: FIRST AID MEASURES

EYES: Flush with water for at least 15 minutes, and call physician if problems persist.

SKIN: Product may leave a sticky residue, and mild irritation if prolonged exposure. Scrub with soapy water until adhesive is removed.

INGESTION: Do not eat. If victim is conscious give two glasses of water and induce vomiting. Call physician.

SECTION 5: FIRE-FIGHTING MEASURES

The material is not flammable.

FLASH POINT: None.

AUTO-IGNITION TEMPERATURE: None as supplied.

EXTINGUISHING MEDIA: Not applicable.

HAZARDOUS DECOMPOSITION PRODUCTS: On burning dry film, some SO₂, and Carbon di/mon oxides will be formed as well as other noxious and toxic fumes upon combustion – do not breath combustion products.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: If material is wet, scrape into disposal containers. If material is dry pick up pieces and dispose of in accordance with local regulations; material and all components are non-toxic and normal landfill will most often be acceptable.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in original packaging below 35°C. Protect from freezing. There are no special handling instructions.

EMSEAL CORPORATION LTD

120 Carrier Drive
Rexdale, ON M9W 5R1
PH : 416-740-2090, FX : 416-740-0233



www.emseal.com

EMSEAL JOINT SYSTEMS LTD

23 Bridle Lane, Suite 3
Westborough, MA 01581-1228
PH: 508-836-0280, FX: 508-836-0281

MATERIAL SAFETY DATA SHEET

PRODUCT: Top Coat 200

MSDS DATE: 2006/11/10

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not required

EYE PROTECTION: Safety goggles to protect against splashing.

SKIN PROTECTION: Gloves are suggested when handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: High viscosity dark brown liquid.

ODOR: Slight characteristic odor.

PERCENT SOLIDS BY WEIGHT: 67%

PHYSICAL STATE: Solid

PERCENT VOLATILE: < 1% wt/wt

Density: 1.03g/cm³

Decomposition: > 100°C

SOLUBILITY IN WATER: Miscible in water as supplied. Insoluble when dry.

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions – avoid temperatures in excess of 100°C, temperatures below 0°C, strong acids and bases.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Will cause eye irritation if not washed immediately. Could also cause gastro-intestinal problems if ingested in large quantity.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Unknown.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: When dry usually may be disposed of in landfill; check with local regulations.

SECTION 14: TRANSPORT INFORMATION

Not hazardous – safe for non-hazardous shipping.

SECTION 15: REGULATORY INFORMATION

Unknown.

SECTION 16: OTHER INFORMATION

None.