



FIELD APPLIED MIN. 3/4 IN (19.1mm)
 DEEP INJECTED SEALANT BAND AND CORNER
 BEAD ALONG SIDE OF DSM AS SHOWN - BOTH SIDES
 (SILICONE SUPPLIED BY EMSEAL)

APP. 3/4 IN
 [19.1mm]

WATERTIGHT FACTORY
 APPLIED TRAFFIC-GRADE
 SILICONE BELLOWS

1/4 IN
 [6.4mm]

EMCRETE ELASTOMERIC
 NOSING MATERIAL

4 IN
 [101.6mm]

EPOXY ADHESIVE
 BOTH SIDES

IMPREGNATED EXPANDING FOAM
 ANCHORING SYSTEM AND
 SHOCK/SOUND ATTENUATING BAFFLE

3 3/4 IN
 [95.3mm]

MOVEMENT: ±50%
 + 1 7/8 IN (48mm)
 - 1 7/8 IN (48mm)

EMSEAL JOINT SYSTEMS LTD.

3 3/4 INCH DSM - DECK TO DECK WITH EMCRETE

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS
 PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL
 BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT. THE RIGHT TO
 REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT
 SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE
 DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY: JPR	DATE: 2015/08/06	SCALE: N.T.S.	SHEET No: 1 OF 1
------------------	---------------------	------------------	---------------------

PART NUMBER:
 DSM_0375_DD_CONC_EMCRETE