



WATERTIGHT FACTORY  
APPLIED TRAFFIC-GRADE  
SILICONE BELLOWS

EPOXY ADHESIVE  
BOTH SIDES

FIELD APPLIED MIN. 3/4 IN (19.1mm)  
DEEP INJECTED SEALANT BAND AND CORNER  
BEAD ALONG SIDE OF DSM AS SHOWN - BOTH SIDES  
(SILICONE SUPPLIED BY EMSEAL)

IMPREGNATED EXPANDING FOAM  
ANCHORING SYSTEM AND  
SHOCK/SOUND ATTENUATING BAFFLE

1 3/4 IN

5/8 IN

MOVEMENT: ±50%  
+ 5/16 IN (8mm)  
- 5/16 IN (8mm)

EMSEAL JOINT SYSTEMS LTD.

DSM-0063

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE  
AND IS PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY  
UNAUTHORIZED USE WILL BE PROSECUTED. THIS DRAWING IS  
PROTECTED BY COPYRIGHT, THE RIGHT TO REPRODUCE IN ANY FORM  
BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT SYSTEMS LTD. ANY  
UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE  
DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY: SWR	DATE: 2016/04/01	SCALE: N.T.S.	SHEET No: 1 OF 1
------------------	---------------------	------------------	---------------------

PART NUMBER: DSM\_0063