

FIRE-RETARDANT-ACRYLIC-INFUSED FOAM

GLASS

FACTORY APPLIED SILICONE FACING

2 3/4 IN
[69.9mm]

SILICONE EDGE FIELD-TUCKED AT
SUBSTRATE(S) TO PRESERVE
SMOOTH FACE

2 IN
[51.1mm]

FLASHING

GYPSUM WALLBOARD

STEEL STUD

EMSEAL JOINT SYSTEMS LTD.

QUIETJOINT AT WALL PARTITION TO GLASS

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT, THE RIGHT TO REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY:	DATE:	SCALE:	SHEET
ORK	2016/11/09	N.T.S.	No: 1 OF 1

PART NUMBER:
SHG_0275_WW_IC_FLASH_GYP_GLASS