



FACTORY APPLIED SILICONE TO SPLINE CORNER BEAD

WATERTIGHT FACTORY APPLIED TRAFFIC-GRADE SILICONE BELLOWS

SAND-BLASTED ALUMINUM COVERPLATE ALSO AVAILABLE IN SAND-BLASTED STAINLESS STEEL OTHER FINISHES BY REQUEST

3/8 IN
5 IN

16 1/2 IN

IMPREGNATED EXPANDING FOAM ANCHORING SYSTEM AND SHOCK/SOUND ATTENUATING BAFFLE

SELF-TAPPING STAINLESS STEEL SCREW 12 O.C.

CENTRAL STIFFENING SPLINE

9 IN

EPOXY ADHESIVE

FIELD APPLIED MIN. 3/4 (19.1mm) DEEP INJECTED SEALANT BAND AND CORNER BEAD

MOVEMENT ± 50%
+ 4 1/2 IN (114mm)
- 4 1/2 IN (114mm)

NOTE: 3/8 IN (9.5mm) COVERPLATES FOR VEHICLE AND PEDESTRIAN-TRAFFIC USE (FOR PEDESTRIAN-TRAFFIC ONLY, USE 1/4 (6.4mm) COVERPLATE)

EMSEAL JOINT SYSTEMS LTD.

SJS - 900 DECK TO DECK EXPANSION JOINT

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT, THE RIGHT TO REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY: SPA	DATE: 2015/11/10	SCALE: N.T.S.	SHEET No: 1 OF 1
PART NUMBER: SJS_9_DD_CONC_3-8_PLATE_LONG_CHAMFER			