



FIELD APPLIED MIN. 3/4 IN (19.1mm)  
DEEP INJECTED SEALANT BAND AND CORNER  
BEAD ALONG SIDE OF DSM AS SHOWN - BOTH SIDES  
(SILICONE SUPPLIED BY EMSEAL)

3 3/4 IN  
[95.2mm]

3 1/2 IN  
[88.9mm]

WATERTIGHT FACTORY  
APPLIED TRAFFIC-GRADE  
SILICONE BELLOWS

1/4 IN  
[6.4mm]

EPOXY ADHESIVE  
BOTH SIDES

IMPREGNATED EXPANDING FOAM  
ANCHORING SYSTEM AND  
SHOCK/SOUND ATTENUATING BAFFLE

MOVEMENT: ±50%  
+1 3/4 IN (45mm)  
-1 3/4 IN (45mm)

**EMSEAL JOINT SYSTEMS LTD.**

**3 1/2 INCH DSM-DS - WALL TO WALL INSIDE CORNER BELOW GRADE**

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT, THE RIGHT TO REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY:	DATE:	SCALE:	SHEET
SPA	2015/08/21	N.T.S.	No: 1 OF 1

PART NUMBER:  
DSM\_DS\_0350\_WW\_IC\_CONC\_BELOW\_GRADE