

FIELD APPLIED MIN. 3/4 IN (19.1mm)  
DEEP INJECTED SEALANT BAND AND CORNER BEAD  
ALONG SIDE OF DSM AS SHOWN – BOTH SIDES  
(SILICONE SUPPLIED BY EMSEAL)

IMPREGNATED EXPANDING FOAM  
ANCHORING SYSTEM AND  
SHOCK/SOUND ATTENUATING BAFFLE

WATERTIGHT FACTORY APPLIED  
TRAFFIC-GRADE SILICONE BELLOWS

SELF LEVELING TRAFFIC GRADE  
SEALANT CONTROL JOINT – BY OTHERS

2 3/4 IN  
[69.9mm]

EPOXY ADHESIVE  
BOTH SIDES

11 13/16 IN  
[300.0mm]

HEAVY DUTY  
STEEL LEG

1/4 IN  
[6.4mm]

EPOXY SETTING  
BED

2 1/2 IN  
[63.5mm]

DECK WATERPROOFING OVERLAY  
FULLY ADHERED TO FP SIDE FLASHING SHEET

FP FLASHING SHEET FULLY-  
ADHERED TO OR EMBEDDED IN  
DECK WATERPROOFING

CHEMICAL ANCHORING  
SYSTEM

MOVEMENT: ±50%  
+ 1 1/4 IN (32mm)  
- 1 1/4 IN (32mm)

## EMSEAL JOINT SYSTEMS LTD.

### DSM-FP-0250-305 DECK TO WALL EXPANSION JOINT

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS  
PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL  
BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT. THE RIGHT TO  
REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT  
SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE  
DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY:	DATE:	SCALE:	SHEET
SWR	2015/12/16	N.T.S.	No: 1 OF 1

PART NUMBER:	DSM_FP_0250_305_DW_CONC
--------------	-------------------------