

APPLY THIN FILLET BEAD OF
SEALANT TO TOP OF TERM BAR
(TYP ALL SIDES)

FACTORY-WELDED
END DAM TERMINATION

TERM BAR INSTALLED
USING NAIL-INS
(TYP ALL SIDES)

EMCRETE ELASTOMERIC
NOSING MATERIAL

HEAT-WELDABLE SANTOPRENE
THERMAFLEX TCR GLAND
(SEE APPLICABLE DETAIL FOR DESIRED
SIZE AND SYSTEM FEATURES)

VARIES

PERFORATED FLANGES ENCAPSULATED IN
NOSING MATERIAL (NOSING NOT SHOWN FOR
CLARITY)

EMSEAL JOINT SYSTEMS LTD.

THERMAFLEX TCR END DAM TERMINATION

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS
PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL
BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT, THE RIGHT TO
REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT
SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE
DIMENSIONS WILL BE PROSECUTED.

DRAWN BY: TRBS	DATE: 2018/01/19	SCALE: N.T.S.	SHEET No: 1 OF 1
-------------------	---------------------	------------------	---------------------

PART NUMBER:
TCR_DD_CONC_END_DAM_TERM_ISO